



# F3 800

MV Agusta è impegnata in una politica di continuo miglioramento dei propri prodotti. Pertanto le informazioni e le caratteristiche tecniche dei veicoli possono essere oggetto di modifiche senza preavviso.



MOTORE	
Tipo	Tre cilindri, 4 tempi, 12 valvole
Distribuzione	Doppio albero a camme in testa, con tenditore meccanico
Cilindrata totale	798 cm <sup>3</sup>
Rapporto di compressione	13,3:1
Avviamento	Elettrico
Alesaggio per corsa	79 mm x 54,3 mm
Potenza max. a giri/min (all'albero)	108 kW (148 CV) a 13.000 giri/min
Coppia massima giri/min	88 Nm (8,97 kgm) a 10.600 giri/min
Raffreddamento	A liquido e olio con radiatori separati
Accensione - Iniezione	Sistema integrato di accensione-iniezione MVICS (Motor & Vehicle Integrated Control System) con sei iniettori. Centralina di controllo motore Eldor EM2.0; corpo farfallato full ride by wire Mikuni; bobine pencil-coil dotate di tecnologia "ion-sensing", controllo della detonazione e e misfire. Controllo di coppia con 4 mappe Traction Control ad 8 livelli di intervento
Sistema cambio elettronico	MV EAS 2.1 (Electronically Assisted Shift Up & Down)
Frizione	Multidisco in bagno d'olio con dispositivo antisaltellamento meccanico
Cambio velocità	Estraibile a sei velocità con ingranaggi sempre in presa
Rapporti primaria	22/41
Rapporti cambio	
Prima: Velocità	13/37
Seconda: Velocità	16/34
Terza: Velocità	18/32
Quarta: Velocità	19/30
Quinta: Velocità	21/30
Sesta: Velocità	22/29
Rapporto finale di trasmissione	17/43

IMPIANTO ELETTRICO	
Tensione impianto	12 V
Alternatore	350 W a 5000 giri/min
Batteria	12 V - 8,6 Ah

DIMENSIONI E PESO	
Interasse	1380 mm
Lunghezza totale	2030 mm
Larghezza max.	730mm
Altezza sella	830 mm
Altezza min. da terra	120 mm
Avancorsa	99 mm
Peso a secco	173 kg
Capacità serbatoio carburante	16,5 l

PRESTAZIONI	
Velocità max.*	240,0 km/h

TELAIO	
Tipo	Tubolare a traliccio in acciaio ALS
Materiale piastre fulcro forcellone	Lega di alluminio

SOSPENSIONE ANTERIORE	
Tipo	Forcella Marzocchi oleodinamica a steli rovesciati con sistema di regolazione esterno e separato del freno in estensione, in compressione e del precarico molla
Ø Steli	43 mm
Corsa sull'asse gambe	125 mm

SOSPENSIONE POSTERIORE	
Tipo	Progressiva, monoammortizzatore Sachs regolabile in estensione, in compressione e nel precarico molla
Materiale forcellone oscillante monobraccio	Lega di alluminio
Corsa ruota	123 mm

FRENI	
Anteriore	A doppio disco flottante (Ø 320 mm) con fascia frenante e flangia in acciaio
Pinza freno anteriore	Radiale monoblocco Brembo a 4 pistoncini (Ø 34 mm)
Posteriore	A disco in acciaio (Ø 220 mm)
Pinza freno posteriore	Brembo a 2 pistoncini (Ø 34 mm)
Sistema ABS	Bosch 9 PLUS Race Mode con RLM (Rear wheel Lift-up Mitigation)

CERCHI	
Anteriore: Materiale / dimensioni	Lega di alluminio 3,50 " x 17 "
Posteriore: Materiale / dimensioni	Lega di alluminio 5,50 " x 17 "

PNEUMATICI	
Anteriore	120/70 - ZR 17 M/C (58 W)
Posteriore	180/55 - ZR 17 M/C (73 W)

CARROZZERIA	
Materiali	Termoplastici - Sottocarena in alluminio

EMISSIONI	
Norma ambientale	Euro 4
Consumo carburante combinato	6.4 l/100 km
Emissioni di CO <sub>2</sub>	157 g/km



ROSSO AGO/ARGENTO AGO



\* Velocità raggiungibile in pista.



# F3 800

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.



ENGINE	
Type	Three cylinder, 4 stroke, 12 valve
Timing system	"D.O.H.C" with mechanical chain tensioner
Total displacement	798 cm <sup>3</sup> (48.7 cu. in.)
Compression ratio	13.3:1
Starting	Electric
Bore x stroke	79 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)	108 kW (148 hp) at 13.000 r.p.m.
Max. torque - r.p.m.	88 Nm (8.97 kgm) at 10.600 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	Integrated ignition - injection system MVICS (Motor & Vehicle Integrated Control System) with six injectors Engine control unit Eldor EM2.0, throttle body full ride by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire Torque control with four maps, Traction Control with eight levels of intervention
Electronic quick shift	MV EAS 2.1 (Electronically Assisted Shift Up & Down)
Clutch	Wet, multi-disc slipper clutch
Transmission	Cassette style; six speed, constant mesh
Primary drive	22/41
Gear ratio	
First gear:	13/37
Second gear:	16/34
Third gear:	18/32
Fourth gear:	19/30
Fifth gear:	21/30
Sixth gear:	22/29
Final drive ratio	17/43

ELECTRICAL EQUIPMENT	
Voltage	12 V
Alternator	350 W at 5000 r.p.m.
Battery	12 V - 8.6 Ah

DIMENSIONS AND WEIGHT	
Wheelbase	1380 mm (54.33 in.)
Overall length	2030 mm (79.92 in.)
Overall width	730 mm (28.74 in.)
Saddle height	830 mm (32.68 in.)
Min. ground clearance	120 mm (4.72 in.)
Trail	99 mm (3.89 in.)
Dry weight	173 kg (381.4 lbs.)
Fuel tank capacity	16,5 l (4.36 U.S. gal.)

PERFORMANCE	
Maximum speed*	240.0 km/h (149.1 mph)

FRAME	
Type	ALS Steel tubular trellis
Rear swing arm pivot plates material	Aluminium alloy

FRONT SUSPENSION	
Type	Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload external and separate adjustment
Fork dia.	43 mm (1.69 in.)
Fork travel	125 mm (4.92 in.)

REAR SUSPENSION	
Type	Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material	Aluminium alloy
Wheel travel	123 mm (4.84 in.)

BRAKES	
Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper	Brembo radial-type monobloc, with 4 pistons Ø 34 mm (Ø 1.34 in.)
Rear brake	Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper	Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System	Bosch 9 Plus with Race Mode and RLM (Rear wheel Lift-up Mitigation)

WHEELS	
Front: Material/size	Aluminium alloy 3.50 " x 17 "
Rear: Material/size	Aluminium alloy 5.50 " x 17 "

TYRES	
Front	120/70 - ZR 17 M/C (58 W)
Rear	180/55 - ZR 17 M/C (73 W)

FAIRING	
Material	Thermoplastic - Aluminium belly-pan

EMISSIONS	
Environmental Standard	Euro 4
Combined fuel consumption	6.4 l/100 km
CO <sub>2</sub> Emissions	157 g/km



AGO RED/AGO SILVER



\* Top speed attained on closed course.  
Every country could have a price variation due to local import duties and taxes.